



United States of America
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION LICENSE

Authorizing Official:

Official Mailing Address:

MULTICULTURAL RADIO BROADCASTING LICENSEE, LI Son Nguyen
40 EXCHANGE PLACE SUITE 1010
NEW YORK NY 10005

Supervisory Engineer
Audio Division
Media Bureau

Grant Date: January 21, 2003

Facility Id: 10825

Call Sign: KMNY

This license expires 3:00 a.m.
local time, August 01, 2005.

License File Number: BL-20021003ACF

This License Covers Permit No.: BMP-20010611AEW

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
Local Standard Time (Non-Advanced)

Jan.	7:30 AM	5:45 PM	Jul.	5:30 AM	7:45 PM
Feb.	7:15 AM	6:15 PM	Aug.	5:45 AM	7:15 PM
Mar.	6:45 AM	6:30 PM	Sep.	6:15 AM	6:30 PM
Apr.	6:00 AM	7:00 PM	Oct.	6:30 AM	6:00 PM
May	5:30 AM	7:15 PM	Nov.	7:00 AM	5:30 PM
Jun.	5:15 AM	7:30 PM	Dec.	7:30 AM	5:30 PM

Callsign: KMNY

License No.: BL-20021003ACF

Name of Licensee: MULTICULTURAL RADIO BROADCASTING LICENSEE, LLC

Station Location: HURST, TX

Frequency (kHz): 1360

Station Class: B

Antenna Coordinates:

Day

Latitude: N 32 Deg 46 Min 28 Sec

Longitude: W 96 Deg 57 Min 53 Sec

Night

Latitude: N 32 Deg 46 Min 28 Sec

Longitude: W 96 Deg 57 Min 53 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 50.0 Night: 0.89

Antenna Input Power (kW): Day: 52.5 Night: 0.959

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Current (amperes): Day: 32.4 Night: 4.38

Resistance (ohms): Day: 50 Night: 50

Antenna Registration Number(s):

Day:

Tower No.	ASRN	
1	None	60.7
2	None	60.7
3	None	60.7
4	None	60.7
5	None	60.7
6	None	60.7

Night:

Tower No.	ASRN	
1	None	60.7
2	None	60.7

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 2003 Night: 273.3

Standard RMS (mV/m/km): Day: 2104 Night: 287.2

Augmented RMS (mV/m/km):

Q Factor: Day: Night:

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	0.3390	23.500	0.0000	0.000	0	94.1
2	1.0000	0.000	173.5000	350.700	0	94.1
3	0.4090	23.200	340.7000	351.800	0	94.1
4	0.6470	43.800	99.5000	81.800	0	94.1
5	1.1260	94.400	202.4000	21.900	0	94.1
6	0.3870	83.300	356.0000	7.300	0	94.1

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	94.1
2	1.5520	4.000	202.4000	21.900	0	94.1

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Day Directional Operation:

Twr. No.	Phase (Deg.)	Antenna Monitor Sample Current Ratio
1	20.2	0.427
2	0	1
3	20.6	0.455
4	37.5	0.686
5	81.2	1.145
6	73.4	0.421

Night Directional Operation:

Twr. No.	Phase (Deg.)	Antenna Monitor Sample Current Ratio
1	-5.9	0.669

Night Directional Operation:

Twr. Phase	Antenna Monitor
No. (Deg.)	Sample Current Ratio
5 0	1

Antenna Monitor: POTOMAC INSTRUMENTS 1901

Sampling System Approved Under Section 73.68 of the Rules.

Monitoring Points:

Day Operation:

Radial (Deg. T)	Distance From Transmitter (kM)	Maximum Field Strength (mV/m)
52	2.7	103.97
112	4.7	121.1
177.5	2.4	104.24
338.5	2.65	138.17

Night Operation:

Radial (Deg. T)	Distance From Transmitter (kM)	Maximum Field Strength (mV/m)
52	2.7	38.45
177.5	2.4	68.84
226.5	2.88	35.62
352.5	2.93	28.26

Special operating conditions or restrictions:

- DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM
No. and Type of Elements: Six (6), guyed, uniform cross-section, base-insulated, series-excited vertical radiators.

Ground System consists of 120 equally spaced, buried copper wire radials (#10 AWG), extending 55.1 meters (181 ft) from all towers except where shortened at the property boundary and between towers about base of each copper.

Special operating conditions or restrictions:

2 DESCRIPTION OF AND FIELD INTENSITY MEASURED AT MONITORING POINTS:

Direction of 52 True North. The monitor point is located at north side of cul-de-sac across from 2534 Markland Street on grate, near fire hydrant. Distance to antenna is 2.70 km. The field intensity measured at this point should not exceed 103.97 mV/m, Daytime; 38.45 mV/m, Nighttime.

Direction of 112 True North. The monitor point is located on curb, 30 feet south of entrance to Supreme Systems, Inc. Distance to antenna is 4.74 km. The field intensity measured at this point should not exceed 121.10 mV/m, Daytime.

Direction of 177.5 True North. The monitor point is located on sidewalk, directly across the street from the church on Reinhardt Street. Distance to antenna is 2.40 km. The field intensity measured at this point should not exceed 104.24 mV/m, Daytime; 68.84 mV/m, Nighttime.

Direction of 226.5 True North. The monitor point is located on curb next to fire hydrant near the southwest corner of Tarrant Street and Tusing Street. Distance to antenna is 2.88 km. The field intensity measured at this point should not exceed 35.62 mV/m, Nighttime.

3 Direction of 338.5 True North. The monitor point is located next to curb in front of 2301 Marvel Street. Distance to antenna is 2.65 km. The field intensity measured at this point should not exceed 138.17 mV/m, Daytime.

Direction of 352.5 True North. The monitor point is located on storm grate in middle of cul-de-sac, near the intersection of Pickwick Lane and Pickwick Circle. Distance to antenna is 2.93 km. The field intensity measured at this point should not exceed 28.26 mV/m, Nighttime.

*** END OF AUTHORIZATION ***