

United States of America FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION CONSTRUCTION PERMIT

Official Mailing Address:

NEW SPIRIT REVIVAL CENTER MINISTRIES, INC. 3130 MAYFIELD ROAD CLEVELAND HEIGHTS OH 44118

Facility Id: 25522

Call Sign: WCCD

Permit File Number: BP-20220622AAB

Change transmitter location.

Authorizing Official:

Son Nguyen Supervisory Engineer Audio Division

Media Bureau

Grant Date: June 28, 2023

This permit expires 3:00 a.m. local time, 36 months after the grant date specified above.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Daytime

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

| Jan. | 7:45 AM | 5:15 PM | Jul. 5:00 AM | 8:00 PM |
|------|---------|---------|--------------|---------|
| Feb. | 7:30 AM | 6:00 PM | Aug. 5:30 AM | 7:30 PM |
| Mar. | 6:45 AM | 6:30 PM | Sep. 6:00 AM | 6:30 PM |
| Apr. | 5:45 AM | 7:00 PM | Oct. 6:45 AM | 5:45 PM |
| Мау | 5:15 AM | 7:45 PM | Nov. 7:15 AM | 5:00 PM |
| Jun. | 4:45 AM | 8:00 PM | Dec. 7:45 AM | 5:00 PM |

| Callsign: WCCD Name of Permittee: NEW SPIRIT | Permit No.: BP-20220622AAB REVIVAL CENTER MINISTRIES, INC. | | | | | | | |
|---|---|--|--|--|--|--|--|--|
| Station Location: PARMA, OH | | | | | | | | |
| Frequency (kHz): 1000 | | | | | | | | |
| Station Class: D | | | | | | | | |
| Antenna Coordinates: | | | | | | | | |
| Day | | | | | | | | |
| Latitude: N 41 Deg 21 Mi | n 30 Sec | | | | | | | |
| Longitude: W 81 Deg 40 Mi | n 03 Sec | | | | | | | |
| Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules. | | | | | | | | |
| Nominal Power (kW): Day: | 0.200 | | | | | | | |
| Antenna Mode: Day: | Day: DA | | | | | | | |
| (DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours) | | | | | | | | |
| Antenna Registration Number(s): | | | | | | | | |
| Day: | | | | | | | | |
| Tower No. ASRN | Overall Height (m) | | | | | | | |
| 1 1015771 | | | | | | | | |
| 2 1015772 | | | | | | | | |

3 1015773

| Callsign: W | CCD | | | P | ermit No.: | BP-20220622AAB | | |
|--------------------------|----------------|-------------------|-----------|-----------------------|-----------------------|------------------|--|--|
| DESCRIPTI | ON OF DIR | STEM | | | | | | |
| Theoretic | al RMS (m' | V/m/km): Da | ay: 145.3 | | | | | |
| Standard RMS (mV/m/km): | | | ay: 152.9 | | | | | |
| Augmented RMS (mV/m/km): | | | | | | | | |
| Q Factor: | | | ay: | | | | | |
| Theoretical Parameters: | | | | | | | | |
| Day Directional Antenna: | | | | | | | | |
| Tower No. | Field Ratio | Phasing (Deg.) | | Orientation (Deg.) | Tower Ref Switch * | Height (Deg.) | | |
| 1 | 1.0000 | 0.000 | 0.0000 | 0.000 | 0 | 146.5 | | |
| 2 | 0.6300 | 104.000 | 150.0000 | 270.000 | 0 | 146.5 | | |
| 3 | 0.8600 | 128.000 | 78.9000 | 184.000 | 0 | 78.0 | | |
| | | a | | | | | | |

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Inverse Distance Field Strength: The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

| Azimuth: | Radiation: | |
|----------|------------|------|
| 117.9 | 98.661 | mV/m |
| 186.2 | 25.606 | mV/m |
| 261.6 | 22.344 | mV/m |

Special operating conditions or restrictions:

1 The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

Callsign: WCCD

Special operating conditions or restrictions:

- 2 The ground system consists of 120 equally spaced, buried copper radials 121.9 meters in length, plus 120 interspersed radials 15.2 meters in length about the base of the #2 (W) tower. Tower #3 (S) consists of 120 equally spaced, buried copper radials 65.5 meters in length except where shortened due to property boundaries or where bonded to a transverse copper strap midway between adjacent towers. Tower #1 (E) consists of copper radials which extend to the bonding straps between towers, in addition to the bonding to the ground bus system of the transmitter building.
- The permittee must submit a proof of performance as set forth in either 3 Section 73.151(a) or 73.151(c) of the rules before program tests are authorized. A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules. Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).
- Before program tests are authorized, sufficient data shall be submitted 4 to show that adequate filters, traps and other equipment has been installed and adjusted to prevent interaction, intermodulation and/or generation of spurious radiation products which may be caused by common usage of the same antenna system by Stations WHK, Fac. ID no. 72299, and WCCD, Fac. ID no. 25522, and there shall be filed with the license application copies of a firm agreement entered into by the stations involved clearly fixing the responsibility of each with regard to the installation and maintenance of such equipment. In addition, field observations shall be made to determine whether spurious emissions exist and any objectionable problems resulting therefrom shall be eliminated. Following construction, and prior to authorization of program test under this grant, Stations WHK, Fac. ID no. 72299, and WCCD, Fac. ID no. 25522, shall each measure antenna or common point resistance and submit FCC Form 302 as application notifying the return to direct measurement of power.

*** END OF AUTHORIZATION ***