

REGISTERED MAIL-RETURN RECEIPT REQUESTED

Mr. Louis LePage, Director
Broadcast Applications Engineering
Broadcasting Regulatory Branch
Industry Canada
Jean Edmons Tower North
300 Slater Street
Ottawa, Ontario, Canada KIA OC8

Dear Mr. LePage:

The Commission is in receipt of a proposal to install a LPTV/Translator station as follows:

1. Applicant: WXMI, LLC
2. File Number: BMPCDT-20130617AAT Call Sign: WXMI
3. Channel Number: 17 (DIGITAL)
4. Principal Community to be Served: BATTLE CREEK, MI.
5. Proposed Transmitter Location: 42 12 09 NL
85 07 32 WL
6. Effective Radiated Power: 15 kW
7. Transmitting Antenna: JAM/JA/LS-CF-16 (DIRECTIONAL)
Orientation: 320 DEGREES
Overall Height Above Ground: 95 meters
Overall Height Above Mean Sea Level: 385 meters
8. Average HAAT: 102.9 meters
9. Digital Emission Mask: STRINGENT

In view of the proximity of this proposed site to the Canadian-U.S.A. border, your comments are requested.

Sincerely,

Ron Graser
Media Bureau, Video Division
(202) 418-1600

azimuth	field_value	ant_make	ant_model_num	antenna_id
0	1	JAM	JA/LS-CF-16	19448
10	0.99	JAM	JA/LS-CF-16	19448
20	0.96	JAM	JA/LS-CF-16	19448
30	0.92	JAM	JA/LS-CF-16	19448
40	0.92	JAM	JA/LS-CF-16	19448
45	0.94	JAM	JA/LS-CF-16	19448
50	0.96	JAM	JA/LS-CF-16	19448
60	0.98	JAM	JA/LS-CF-16	19448
70	1	JAM	JA/LS-CF-16	19448
80	0.97	JAM	JA/LS-CF-16	19448
90	0.92	JAM	JA/LS-CF-16	19448
100	0.85	JAM	JA/LS-CF-16	19448
110	0.72	JAM	JA/LS-CF-16	19448
120	0.6	JAM	JA/LS-CF-16	19448
130	0.44	JAM	JA/LS-CF-16	19448
135	0.38	JAM	JA/LS-CF-16	19448
140	0.32	JAM	JA/LS-CF-16	19448
150	0.25	JAM	JA/LS-CF-16	19448
160	0.2	JAM	JA/LS-CF-16	19448
170	0.21	JAM	JA/LS-CF-16	19448
180	0.22	JAM	JA/LS-CF-16	19448
190	0.21	JAM	JA/LS-CF-16	19448
200	0.2	JAM	JA/LS-CF-16	19448
210	0.25	JAM	JA/LS-CF-16	19448
220	0.32	JAM	JA/LS-CF-16	19448
225	0.38	JAM	JA/LS-CF-16	19448
230	0.44	JAM	JA/LS-CF-16	19448
240	0.6	JAM	JA/LS-CF-16	19448
250	0.72	JAM	JA/LS-CF-16	19448
260	0.85	JAM	JA/LS-CF-16	19448
270	0.92	JAM	JA/LS-CF-16	19448
280	0.97	JAM	JA/LS-CF-16	19448
290	1	JAM	JA/LS-CF-16	19448
300	0.98	JAM	JA/LS-CF-16	19448
310	0.96	JAM	JA/LS-CF-16	19448
315	0.94	JAM	JA/LS-CF-16	19448
320	0.92	JAM	JA/LS-CF-16	19448
330	0.92	JAM	JA/LS-CF-16	19448
340	0.96	JAM	JA/LS-CF-16	19448
350	0.99	JAM	JA/LS-CF-16	19448