

**FEDERAL COMMUNICATIONS COMMISSION
445 TWELFTH STREET SW
WASHINGTON DC 20554**

MEDIA BUREAU
AUDIO DIVISION
APPLICATION STATUS: (202) 418-2730
HOME PAGE: www.fcc.gov/mb/audio/

ENGINEER: JOSEPH SZCZESNY
TELEPHONE: (202) 418-2700
FACSIMILE: (202) 418-1410
E-MAIL: joseph.szczesny@fcc.gov

April 25, 2016

Robert H. Walls Jr., GC
Clear Channel Broadcasting Licenses, Inc.
2625 S. Memorial Drive, Suite A
Tulsa, OK 74129

In re: WDAE(AM), St. Petersburg, FL
Facility Identification Number: 74198
Clear Channel Broadcasting Licenses, Inc. (CCBL)
Special Temporary Authority (STA)
BESTA- 20160405AAA


Dear Mr. Walls:

This is in reference to the request filed on April 5, 2016. CCBL requests further extension of the STA originally granted June 3, 1983, and last revised on June 19, 2008, for operation with parameters at variance due to Cuban interference.¹ In support of the request, CCBL states that the interference continues.

Accordingly, the request for extension of STA IS HEREBY GRANTED, and station WDAE may continue to operate with increased nominal operating power, not to exceed 11.2 kW day and 11.0 kW night; and increased antenna input power, not to exceed 11.2 kW day and 11.6 kW night (per attached nighttime DA specifications). This authority is subject to termination upon reduction of power or cessation of operation by the Cuban operation or upon Commission instruction to WDAE to resume licensed operating parameters per BL-20070612ACM. The field strength at each monitor point must be measured monthly to assure proper array operation. It will be necessary to reduce power if interference complaints are received.

This authority expires on **October 25, 2016**.

Sincerely,



Joseph Szczesny, Engineer
Audio Division
Media Bureau

Attachment: Directional Antenna Specifications
cc: Gregory L. Masters., WR LLP (via e-mail)

¹ WDAE is currently licensed to operate on 620 kHz with 5.6 kW (ND) day, and 5.5 kW (DA) night.

Special Temporary Authority

Specifications For Nighttime Directional Operation of WDAE (AM), St. Petersburg, Florida

Frequency: 620 kHz **Nominal Power:** 11 kW **Antenna Input Power:** 11.6 kW

Common Point Current: 15.2 Amperes **Common Point Resistance:** 50 ohms

Transmitter site coordinates (NAD 1927): 27° 52' 37" N, 82° 35' 25" W

Description of Directional Antenna System:

Number and Type of Elements: Two (2) vertical, self-supporting, series-excited steel radiators.

Height above Insulators: 109.7 meters (81.7°)

Overall Height: 113.4 meters

Ground System: Directly underneath each tower is a 21.3 by 21.3 meter ground screen. The screens are supported above sea level at high tide and consist of 120 radial wires running from a point underneath the center of each tower structure to copper bus perimeter conductor surrounding the tower base areas. From the ground screen perimeter conductors, 24 copper pipe conductors extend vertically downward through seawater to the underwater soil level surrounding each tower. A copper strap connecting the ground screens runs in a trench between the towers.

Spacing and Orientation: With Tower #1 (NW) as a reference, Tower #2 (SE) is spaced 128° (171.9 m) on a line bearing 140°.

Theoretical RMS: 993.5 mV/m at 1 km

Augmented RMS: 1052.2 mV/m at 1 km

Q factor: 33.2 mV/m

Theoretical Parameters:

	Tower #1(NW)	Tower #2 (SE)
Field Ratio:	1.000	1.480
Phasing (degrees):	0.0	-69.0

Special Temporary Authority

**Specifications For Nighttime Directional Operation of
WDAE (AM), St. Petersburg, Florida**

Augmentations:

No.	Azimuth	Span	Field Strength
1	20.0	24.0	631.2
2	60.0	56.0	1324.7
3	205.0	50.0	1435.4
4	252.5	19.0	833.8
5	275.0	20.0	419.5
6	287.5	20.0	331.2
7	300.0	20.0	397.4
8	310.0	20.0	436.7
9	320.0	20.0	436.7
10	334.0	28.0	351.0
11	345.0	10.0	304.6
12	355.0	18.0	309.1

Operating Parameters*

	Tower #1(NW)	Tower #2 (SE)
Phase (degrees):	0.0	-62.8
Current Ratio:	1.000	1.396

*As indicated by Potomac Instruments AM-1901 antenna Monitor.

Antenna sampling system approved under Section 73.68 (b) of the rules.

Descriptions Of And Field Intensities At Monitor Points:

Direction of 287.5° True North: Center of driveway to 14239 Puffin Court. Distance from the transmitter site is 9.08 km. The field intensity at this point shall not exceed **55.7 mV/m**.

Direction of 355° True North: Stop sign on the northeast corner of Grand Bahama Drive and Pepperfish Bay Way. Distance from the transmitter site is 15.16 km. The field intensity at this point shall not exceed **37.9 mV/m**.