

Call sign: KBPR

License No.: BLED-880222KG

Frequency (MHz): 90.7

Channel: 214

Class: C1

Hours of Operation: Unlimited

Main Studio Address:

MN-AT TRANSMITTER SITE

Transmitter location (address or description):

6.1 MILES NORTH OF PILLAGER, CASS COUNTY, MINNESOTA.

Remote control point address:

MN-ST JOHN'S POWERHOUSE, ST JOHN'S UNIVERSITY, COLLEGEVILLE

Transmitter: Type accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power (kW): 9.1

Antenna type: (directional or non-directional): Non-directional

Desc: ERI FMH-8AC, 8 BAY CIRCULARLY POLARIZED ANTENNA MOUNTED ON AN ALLIED TOWER MODEL M48.

Antenna coordinates: North Latitude: 46 25 21.0
West Longitude: 94 27 41.0

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the horizontal plane (kW) :	34.0	34.0
Height of radiation center above ground (meters) :	179.0	179.0
Height of radiation center above mean sea level (meters) :	597.0	597.0
Height of radiation center above average terrain (meters) :	207.0	207.0

Overall height of antenna structure above ground (including obstruction lighting, if any) : 206.0 meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

Paragraph 1.0, FCC Form 715 (March 1978):

Antenna structures shall be painted throughout their height with alternate bands of aviation surface orange and white, terminating with aviation surface orange bands at both top and bottom. The width of the bands shall be equal and approximately one-seventh the height of the structure, provided however, that the bands shall not be more than 100 feet nor less than 1 and 1/2 feet in width. All towers shall be cleaned and repainted as often as necessary to maintain good visibility.

Paragraph 3.0, FCC Form 715 (March 1978):

There shall be installed at the top of the structure one 300 m/m electric code beacon equipped with two 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. Where a rod or other construction of not more than 20 feet in height and incapable of supporting this beacon is mounted on top of the structure and it is determined that this additional construction does not permit unobstructed visibility of the code beacon from aircraft at any normal angle of approach, there shall be installed two such beacons positioned so as to insure unobstructed visibility of at least one of the beacons from aircraft at any normal angle of approach. The beacons shall be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.

Paragraph 5.0, FCC Form 715 (March 1978):

At approximately two-fifths of the over-all height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event this beacon cannot be installed in a manner to insure unobstructed visibility of it from aircraft at any normal angle of approach, there shall be installed two such beacons. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

Paragraph 14.0, FCC Form 715 (March 1978):

On levels at approximately four-fifths, three-fifths and one-fifth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

Paragraph 21.0, FCC Form 715 (March 1978):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.