

United States of America

FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

DUPAGE RADIO, LLC 1750 W. OGDEN AVE.

#5502

NAPERVILLE IL 60540

Facility Id: 32227

Call Sign: WCKG

Permit File Number: BP-20190604AAV

Permit to change daytime pattern.

Boshangen

Son Nguyen

Supervisory Engineer Audio Division

Media Bureau

Grant Date: AUG - 5 2019

This permit expires 3:00 a.m. local time, 36 months after the grant date specified above.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Daytime

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

| Jan. | 7:15 | AM | 4:45 | PM | Jul. | 4:30 | AM | 7:30 | PM |
|------|------|----|------|----|------|------|----|------|----|
| Feb. | 6:45 | AM | 5:30 | PM | Aug. | 5:00 | AM | 7:00 | PM |
| Mar. | 6:00 | AM | 6:00 | PM | Sep. | 5:30 | AM | 6:00 | PM |
| Apr. | 5:15 | AM | 6:30 | PM | Oct. | 6:00 | AM | 5:15 | PM |
| May | 4:30 | AM | 7:00 | PM | Nov. | 6:45 | AM | 4:30 | PM |
| Jun. | 4:15 | AM | 7:30 | PM | Dec. | 7:15 | AM | 4:15 | PM |

Callsign: WCKG Permit No.: BP-20190604AAV

Name of Permittee: DUPAGE RADIO, LLC

Station Location: ELMHURST, IL

Frequency (kHz): 1530

Station Class: D

Antenna Coordinates:

Day

Latitude: N 41 Deg 52 Min 03 Sec Longitude: W 87 Deg 55 Min 07 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and

73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 4.0

Antenna Mode: Day: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No. ASRN

1 None 49.77 2 None 49.77 Callsign: WCKG Permit No.: BP-20190604AAV

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 612.23

Standard RMS (mV/m/km): Day: 643.19

Augmented RMS (mV/m/km):

Q Factor:

Day:

Theoretical Parameters:

Day Directional Antenna:

| Tower No. | Field Ratio | Phasing (Deg.) | Spacing (Deg.) | Orientation (Deg.) | Tower Ref Switch * | Height (Deg.) |
|--------------|----------------|-------------------|----------------|--------------------|-----------------------|------------------|
| 1 | 1.0000 | 0.000 | 0.0000 | 0.000 | 0 | 89.6 |
| 2 | 1.1250 | 70.000 | 90.0000 | 135.000 | 0 | 89.6 |

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth: Radiation: 135 155.7 mV/m 315 830 mV/m

Callsign: WCKG Permit No.: BP-20190604AAV

Special operating conditions or restrictions:

The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized. A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the (day) directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules. Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).

- 2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- 4 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.
- Ground system consists of 120 equally spaced, buried, copper radials, each 49.1 meters in length except where terminated by property boundaries or where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers, plus a copper ground screen 7.3 meters square, about the base of each tower.

*** END OF AUTHORIZATION ***