



United States of America  
**FEDERAL COMMUNICATIONS COMMISSION**  
**AM BROADCAST STATION CONSTRUCTION PERMIT**

Authorizing Official:

Official Mailing Address:

\_\_\_\_\_  
 BIRACH BROADCASTING CORPORATION  
 21700 NORTHWESTERN HWY STE 1190  
 TOWER 14  
 SOUTHFIELD MI 48075  
 \_\_\_\_\_

*Son Nguyen*  
 \_\_\_\_\_  
 Son Nguyen  
 Supervisory Engineer  
 Audio Division  
 Media Bureau

Facility Id: 1088  
 Call Sign: WEW  
 Permit File Number: BP-20190614AAQ

Grant Date: **AUG 22 2019**  
 This permit expires 3:00 a.m.  
 local time, 36 months after the  
 grant date specified above.

Permit to change site and patterns.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:  
 Local Standard Time (Non-Advanced)

Jan.	7:15 AM	5:00 PM	Jul.	4:45 AM	7:30 PM
Feb.	6:45 AM	5:30 PM	Aug.	5:15 AM	7:00 PM
Mar.	6:15 AM	6:00 PM	Sep.	5:45 AM	6:15 PM
Apr.	5:30 AM	6:30 PM	Oct.	6:15 AM	5:30 PM
May	4:45 AM	7:00 PM	Nov.	6:45 AM	4:45 PM
Jun.	4:30 AM	7:30 PM	Dec.	7:15 AM	4:45 PM

Callsign: WEW

Permit No.: BP-20190614AAQ

Name of Permittee: BIRACH BROADCASTING CORPORATION

Station Location: ST. LOUIS, MO

Frequency (kHz): 770

Station Class: B

Antenna Coordinates:

Day

Latitude: N 38 Deg 38 Min 33 Sec

Longitude: W 90 Deg 01 Min 50 Sec

Night

Latitude: N 38 Deg 38 Min 33 Sec

Longitude: W 90 Deg 01 Min 50 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 10.0 Night: 0.200

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No.	ASRN	
1	None	60.7
2	None	60.7

Night:

Tower No.	ASRN	
1	None	60.7
2	None	60.7

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 945.95 Night: 130.42  
 Standard RMS (mV/m/km): Day: 993.8 Night: 137.35  
 Augmented RMS (mV/m/km):  
 Q Factor: Day: Night:

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	TL/S
2	0.6800	-90.000	90.0000	205.000	0	TL/S

\* Tower Reference Switch

- 0 = Spacing and orientation from reference tower
- 1 = Spacing and orientation from previous tower

Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)

Tower No.	A	B	C	D
1	55.0	20.00	.00	.00
2	55.0	20.00	.00	.00

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	TL/S
2	0.9000	-66.000	132.0000	245.500	0	TL/S

\* Tower Reference Switch

- 0 = Spacing and orientation from reference tower
- 1 = Spacing and orientation from previous tower

Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)

Tower No.	A	B	C	D
1	55.0	20.00	.00	.00
2	55.0	20.00	.00	.00

## Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

## Day:

Azimuth:	Radiation:
25.5	264.9 mV/m

## Night:

Azimuth:	Radiation:
35	14.5 mV/m
96	14.5 mV/m
245.5	160.9 mV/m

## Special operating conditions or restrictions:

- 1 The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized.  
A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the (day) and (night) directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.  
Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).
- 2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- 3 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- 4 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.
- 5 Ground system consists of 120 equally spaced, buried, copper radials about the base of each tower, each 97.3 meters in length except where terminated by property boundaries or where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers.

Special operating conditions or restrictions:

- 6 Before program tests are authorized, permittee shall submit sufficient current distribution measurement data to establish clearly that the current distribution approximates that of an antenna with electrical height of 75 degrees, for both towers as proposed.

\*\*\* END OF AUTHORIZATION \*\*\*