

## **United States of America**

# FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

SALEM COMMUNICATIONS HOLDING CORPORATION 4880 SANTA ROSA ROAD

CAMARILLO CA 93012

Facility Id: 1185

Call Sign: WBZW

Permit File Number: BP-20191114AAX

Son Nguyen

Supervisory Engineer

Audio Division

Media Bureau

Grant Date: MAR - 3 2020

This permit expires 3:00 a.m. local time, 36 months after the grant date specified above.

This Permit Modifies Permit No.: BZ-20100714ACX

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Daytime with Secondary nighttime

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

Jan.	7:15 AM	1 5:45	PM	Jul.	5:30	AM	7:30	PM
Feb.	7:00 AM	6:15	PM	Aug.	6:00	AM	7:00	PM
Mar.	6:30 AM	6:30	PM	Sep.	6:15	AM	6:30	PM
Apr.	6:00 AM	6:45	PM	Oct.	6:30	AM	6:00	PM
May	5:30 AM	7:15	PM	Nov.	6:45	AM	5:30	PM
Jun.	5:30 AN	7:30	PM	Dec.	7:15	AM	5:30	PM

Name of Permittee: SALEM COMMUNICATIONS HOLDING CORPORATION

Station Location: FAIRVIEW SHORES, FL

Frequency (kHz): 1520

Station Class: D

### Antenna Coordinates:

Day

Latitude: N 28 Deg 34 Min 12 Sec Longitude: W 81 Deg 25 Min 60 Sec

Night

Latitude: N 28 Deg 34 Min 12 Sec Longitude: W 81 Deg 25 Min 60 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW):

Day: 4.0 Night: 0.008

Antenna Mode:

Day: DA

Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

## Antenna Registration Number(s):

## Day:

Tower No. ASRN Overall Height (m)

1 1247871

2 1247872

### Night:

Tower No. ASRN Overall Height (m)

1 1247871

2 1247872

### DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 705.62

Night: 31.56

Standard RMS (mV/m/km):

Day: 741.2

Night: 34.76

Augmented RMS (mV/m/km):

Q Factor:

Day:

Night:

### Theoretical Parameters:

## Day Directional Antenna:

Height (Deg.)	Tower Ref Switch *	Orientation (Deg.)	Spacing (Deg.)	Phasing (Deg.)	Field Ratio	Tower No.
168.8	0	0.000	0.0000	0.000	1.0000	1
168.8	0	86.100	168.8400	-24.000	0.4800	2

#### \* Tower Reference Switch

- 0 = Spacing and orientation from reference tower
- 1 = Spacing and orientation from previous tower

#### Theoretical Parameters:

## Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	168.8
2	0.4800	-24.000	168.8400	86.100	0	168.8

## \* Tower Reference Switch

- 0 = Spacing and orientation from reference tower
- 1 = Spacing and orientation from previous tower

## Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

### Day:

Azimuth:	Radiation:	
85	490.46	mV/m
244	382.31	mV/m
289	382.31	mV/m

Special operating conditions or restrictions:

Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.

- A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.
- The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized.

  A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the day directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.

  Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).
- Before program tests are authorized, sufficient data shall be submitted to show that adequate filters, traps and other equipment has been installed and adjusted to prevent interaction, intermodulation and/or generation of spurious radiation products which may be caused by common usage of the same antenna system by Stations WBZW, Fairview Shores, FL, 1520 kHz, Facility ID 1185, and WRSO, Orlovista, FL, 810 kHz, Facility ID 129548, and there shall be filed with the license

application copies of a firm agreement entered into by the two (2) stations involved clearly fixing the responsibility of each with regard to the installation and maintenance of such equipment. In addition, field observations shall be made to determine whether spurious emissions exist and any objectionable problems resulting therefrom shall be eliminated. Following construction, and prior to authorization of program test under this grant, Stations WBZW, Fairview Shores, FL, 1520 kHz, Facility ID 1185, and WRSO, Orlovista, FL, 810 kHz, Facility ID 129548 shall each measure antenna or common point resistance and submit FCC Form 302 as application notifying the return to direct measurement of power.

Special operating conditions or restrictions:

- Prior to construction of the tower authorized herein, permittee shall notify AM Stations WIWA, Eatonville, FL, 1270 kHz, Facility ID 57931 and WTLN, Orlando, FL, 990 kHz, Facility ID 23442 so that, if necessary that AM stations: may determine operating power by a method described in Section 73.51(a)(1) or (d), and/or request temporary authority from the Commission in Washington, D.C. to operate with parameters at variance in order to maintain monitoring point field strengths within authorized limits. Permittee shall be responsible for installation and continued maintenance of detuning apparatus necessary to prevent adverse effects upon the radiation pattern of the AM stations. Both prior to construction of the tower and subsequent to the installation of all appurtenances thereon, a partial proof of performance, as defined by Section 73.154(a) of the Commission's Rules, shall be conducted to establish that the AM array has not been adversely affected and prior to or simultaneous with the filing of the application for license to cover this permit, the results submitted to the Commission.
- 7 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.
- Before program test authority is authorized by the Commission: sufficient radiofrequency (RF) electromagnetic field measurements taken at the tower fence shall be submitted to show that the new power level RF radiation is in compliance with the American National Standards Institute Guidelines (OET Bulletin No. 65. August 1997); or a fence must be erected at such distances and in such a manner as to prevent the exposure human exposure to radiofrequency electromagnetic fields in excess of the FCC Guidelines (OET Bulletin No. 65. Edition 97-01, August 1997). The fence must be of a type which will preclude casual or inadvertent access, and must include warning signs at appropriate intervals which describe the nature of the hazard. Permittee shall submit documentation of compliance with this special operating condition along with the Form 302, application for license and the request for program test authority.
- 9 Ground system consists of 120 equally spaced, buried, copper radials about the base of each tower, each 92.5 meters in length except where terminated by property boundaries or where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers.

\*\*\* END OF AUTHORIZATION \*\*\*